

STONELOCK

GATEWAY

INTEGRATIONS FEATURE MATRIX	Version	Required Licence	Certified	Real-time Integration	Bi-Directional Integration				Badge Offset	Facility Code	Embossed Field	Remote Integration	Redundant Server
					Events	Integrated User Management							
						Priority User	Card Only Privilege	Re-Enroll Trigger					
AMAG - Symmetry	9.3	DataConnect and Reader License	★	●	●	●	●						
Avigilon - Access Control Manager (ACM)	6.01, 6.20	AC-SW-LIC-XML	N/A	●	N/A	●	●	●	●	●	●	●	
Genetec - Security Center	5.9, 5.10	GSC-1SDK-SL-Gateway	★	●		●	●	●	●				
Honeywell - Enterprise Buildings Integrator (EBI)	R600	EBIX-DBR006 or EBIX-DBR050 or EBIX-DBR400	N/A	●	●	●	●	●	●			●	
Honeywell - ProWatch	5.0	PWDBUT PWDBUT-API	N/A	●		●	●	●	●				
Kantech - EntraPass (Corporate, Global)	8.2	E-COR-CONNECT or E-GLO-CONNECT	N/A	●	●	●	●	●				●	
LenelS2 - OnGuard	8.0	IPC-094-STNLK22-B	★	●		●	●	●	●	●	●		
Software House - C-Cure 9000	2.80, 2.90, 3.00	CC9000-STONELOCK	N/A	●		●	●	●	●				

Badge Offset: A badge offset number can optionally be defined within each card type. This number is then added to the user card number.

Facility Code: A facility code must be defined in the StoneLock web client for each card type in order for the user credentials to work properly.

Remote Server: The StoneLock integration can be configured to run on a separate machine from the access control system software.

Redundant Server: The StoneLock integration can be configured to run on the primary access control server with automatic fail over to a secondary sever.

Embossed Field: When the embossed field contains data on the access control partner side, the data from the embossed field is displayed in the StoneLock web client. If the embossed field is empty on the access control partner side, the data from the card number (badge) field will be displayed in the StoneLock web client.